

Plaster Delay Set

Plaster Retarder

Plaster Delay Set is a dry, powdered admixture packaged in a ready-to-use, **water-soluble bag**. It is designed to slow down the set of plaster. It will not discolor or affect the final strength of the plaster. Plaster Delay Set is very predictable in its use. Used as directed, one bag will retard the set of plaster for about one hour, depending on temperature. Up to three bags may be used. It does not contain chlorides, nitrites, nitrates, or clay.

MEETS STANDARDS:

There are no applicable standards for this product.

PACKAGING:

SIZE	10 oz. Bags
BAGS/CASE	40
CASES/PALLET	35



No 95450

ADVANTAGES

- Easy storage & transport
- Reduced risk of shrinkage cracks
- Extended plaster workability
- Improved pool finishes
- Does not weaken plaster
- Does not discolor plaster

INSTRUCTIONS

- When blending plaster at the job site, use 1 bag of Plaster Delay Set per every 4 bags of cement in the mix, for 1 hour of retardation.
- When using pre-blended plaster, use 1 bag of Plaster Delay Set per 1,000 lb., for 1 hour of retardation.
- Prepare pool plaster mix using all ingredients, including water. Begin mechanical mixing before adding Plaster Delay Set.
- Add the water-soluble bag to the plaster mix in the mixer & continue mixing for 5 minutes.
- If adding Plaster Delay Set to dry plaster blends for sale, use 2.66 oz./cwt of cement for about 1 hour set retardation.

FAQ

- Q:** Can Plaster Delay Set be redosed?
A: Yes. Redosing should occur before initial set has begun.
- Q:** Can Plaster Delay Set be used with gray Portland cement?
A: Yes. Plaster Delay Set is very effective with this type of cement.
- Q:** Does Plaster Delay Set affect the durability of the plaster?
A: No.
- Q:** Will Plaster Delay Set discolor the plaster?
A: No. Plaster Delay Set is a white material that will not cause problems with integral colors in the plaster mix.

COMPATIBILITY

Plaster Delay Set is compatible with most concrete and cement admixtures. When using more than one admixture, each product should be dispensed separately. Plaster Delay Set does not contain calcium chloride, nitrates, or other potentially corrosive materials. Store in a dry location, protected from breakage, deterioration, and contamination. It is not subject to damage from freezing temperatures.

WARRANTY

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Fritz-Pak Corporation and users should make their own tests to determine the suitability of these products for their own particular purposes. Because of numerous factors affecting results, Fritz-Pak Corporation makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for purpose. Statements herein, therefore, should not be construed as representations or warranties. The responsibility of Fritz-Pak Corporation for claims arising out of breach of warranty, negligence, strict liability, or otherwise are limited to the purchase price of the materials.

© 2023 Fritz-Pak Corporation