

Water Conditioner

Water Conditioner is a dry powdered admixture packaged in a ready-to-use, water-soluble bag. It is intended for use in volumetric concrete mixers to prevent false-set problems. False-set is a term used to describe the stiffening of the concrete within one minute after water is added. It is not a “hard set”. It happens more frequently in volumetric mixers because mixing times are not long enough and don’t go past the false-set condition.

MEETS STANDARDS

There are not applicable standards for this product.

PACKAGING:

SIZE	4 oz. Bags
BAGS/CASE	100
CASES/PALLET	24

False-Set Admixture



No 98420

ADVANTAGES

- Reduced false-setting concrete
- Easy storage & transportation
- No effect on set times
- No effect on concrete strength



DOSAGE

One 4-oz bag of Water Conditioner will treat 400 gallons (1,500 liters) of water.

DIRECTIONS

1. Determine the amount of Water Conditioner required. See Dosage section above.
2. Remove the protective outer bag, add the inner water-soluble bag and contents into water tank and let dissolve for at least 5 minutes.
3. Add water to concrete mix as per your mix design. Unused water may be left in the tank.

FREQUENTLY ASKED QUESTIONS

Q. Why does false set occur in volumetric mixers but not in regular ready mix concrete?

A. False set is a rapid hardening of the concrete shortly after adding water. This false set is not a hard set and in regular ready mix concrete, the extended mixing simply breaks up this false set.

Q. Why does false set occur?

A. In the manufacture of cement, gypsum is added to control the set. The gypsum is normally added in the final milling process. If in the final milling the temperature of the cement gets too hot, the gypsum will dehydrate forming anhydrate or hemihydrate (plaster of Paris). When water is added the plaster of Paris hardens very fast and gives the appearance of a false set.

Q. Why doesn't false set happen all the time?

A. False set is more common in the summer time and when cement plants are working at full capacity.

Q. Why it is important to control the false set in volumetric mixers?

A. Because when the false set appears, it is very difficult for the contractor to work the concrete. If excess water or superplasticizer is added to the concrete to reduce the effects, this can cause a weaker concrete or increased cost of admixtures.

COMPATIBILITY & PRECAUTIONS

Water Conditioner is compatible with most concrete and cement admixtures. When using more than one admixture, each product should be dispensed separately. Water Conditioner does not contain calcium chloride, nitrates, or other potentially corrosive materials. Store in a dry location, protected from breakage, deterioration, and contamination. Water Conditioner is not subject to damage from freezing temperatures.

WARRANTY

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Fritz-Pak Corporation and users should make their own tests to determine the suitability of these products for their own particular purposes. Because of numerous factors affecting results, Fritz-Pak Corporation makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for purpose. Statements herein, therefore, should not be construed as representations or warranties. The responsibility of Fritz-Pak Corporation for claims arising out of breach of warranty, negligence, strict liability, or otherwise are limited to the purchase price of the materials.

© 2023 Fritz-Pak Corporation