FRITZ-PAK
fritzpak.com

CONTROL FINISH

FINISHING AID

Fritz-Pak Control Finish improves concrete surface finishing characteristics without retempering with water. This reduces common surface problems, including plastic shrinkage cracks, crusting, and crazing. Control Finish comes packaged in our signature water-soluble bags for easy mixing at the job site.

ADVANTAGES

- No Surface Retempering
- Enhanced concrete color
- Reduced risk of crazing or crusting due to wind
- Small packaging fits inside narrow-mouth sprayers

CERTIFICATIONS

There are no applicable standards for this product.

PACKAGING:

ITEM NUMBER	WEIGHT	BAGS PER CASE	CASES PER PALLET
97000	18 ounces	30	35
97010	50 pounds	1	40

FRITZ-PAK
fritzpak.com

DOSAGE

Mix one 9-ounce package in 1.5 gallons (5.7 liters) of water. Mix both 9-ounce packages in 3 gallons (11.4 liters) of water. For a stronger solution, both inner bags may be added to 1.5 gallons (5.7 liters). One full package of Control Finish creates a solution that covers 1,000 square feet (100 square meters).

DIRECTIONS

1. Determine the amount of Control Finish required for the area you want to cover.

2. Each Control Finish package is double bagged. Remove the protective outer bag and add one or both of the entire Fritz-Pak inner packs to water in a spraying can or power trowel tank. The bags dissolve easily with agitation.

3. Mix or shake for 3-5 minutes to uniformly dissolve. Remix as needed.

4. Prior to troweling, mist Control Finish evenly on the concrete surface. Only a light application is necessary.

FREQUENTLY ASKED QUESTIONS

QUESTIONS	ANSWERS
What is the shelf life of Control Finish?	In the liquid form, it can be used for up to 6 months. Remixing will be necessary after long periods of inactivity. In powdered form, if stored properly, about 2-3 years. If the material ever seems hard or caked, do not use it. It will not break up in the mix.
Will Control Finish affect concrete colors?	Control Finish has recently been reformulated to avoid using dark colored material. If applied lightly and evenly, there should be no effect on concrete color.
Can Control Finish be used with color hardener?	Yes, it is particularly suited to help in the application.
Can Control Finish be reapplied?	Yes, you can reapply as needed as you move through the finishing area.
Will it retard the set of concrete?	Not if applied correctly. If excess amounts are sprayed, and accumulate on the surface, some surface retardation may occur.

COMPATIBILITY & PRECAUTIONS

When using Control Finish, avoid heavy or uneven applications, which may slightly discolor and retard the concrete surface. Like all Fritz-Pak concrete admixtures, Control Finish should be stored in a dry location where it will be protected from breakage, deterioration, and contamination. Control Finish can be used with concrete containing most common admixtures, and it is not subject to damage from freezing temperatures.

WARRANTY

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Fritz-Pak Corporation and users should make their own tests to determine the suitability of these products for their own particular purposes. Because of numerous factors affecting results, Fritz-Pak Corporation makes no warranty of any kind, expressed or implied, including those of merchantability and fitness for purpose. Statements herein, therefore, should not be construed as representations or warranties. The responsibility of Fritz-Pak Corporation for claims arising out of breach of warranty, negligence, strict liability, or otherwise are limited to the purchase price of the materials.

© 2025 Fritz-Pak Corporation